



Cloud speaker MDP810

- 4G (Cat.1) /2G(GPRS)/WIFI communication
- Integrated design, more durable equipment
- Supports TTS, OTA, and advertising corpus
 - Show transaction amount
- Using high-power speakers to ensure sound quality



4G



Speaker



WiFi



Battery



MDP810

Specifications



Processor

ARM CortexA5 500MHZ

Memory

12MB Flash
16MB RAM

Communication

4G(Cat.1)/2G(GPRS)
OptionalWiFi(2.4G)

Audios

wav、mp3、 etc.
Support TTS voice conversion

Keys

1x Volume+/-
1x Power
1x Function

Speaker

4Ω,3W Volume≥110dB

Digital display

Optional6-digit 8-segment LED
display, which can display
numbers,extended characters,etc.

Indicator Light

Power Indicator Status Indicator

Battery

Rechargeable Li-ion Battery
3.7V/2000mAh

Adapter / Power

Optional,Input:
100-240VAC 50Hz/60Hz
Output:5.0V DC,1A

Peripheral Ports

1XType C-USB
1X SIM(or optional 2*SIM)

Dimensions

Terminal:149 x 101 x 40mm

Code Plate

QR code Plate

Working Environment

Temperature:
0°C~50°C(32°F~122°F)
Humidity:
5%~95%(non-condense)

Storage Environment

Temperature:
-20°C~60°C(-4°F~140°F)
Humidity:
5%~95%(non-condense)

Certifications

CCC,BIS,WPC,etc



The configuration and parameters listed on the product page above are subject to the actual product and are subject to change without notice.

Tel: +86-755-86717417 Fax: +86-755-82790632 E-mail: sales@newpostech.com Web: www.newpostech.com